

US009636613B2

(12) United States Patent

Hayslett et al.

(54) PORTABLE WATER BOTTLE ASSEMBLY HAVING A REPLACEABLE FILTER CARTRIDGE

(71) Applicant: Liquidity Corporation, Alameda, CA

D 11H 144 C 1 11 CA (1

(72) Inventors: **David Hayslett**, Campbell, CA (US); **Tomás Colussi**, Oakland, CA (US); **Michael Hawes**, Orinda, CA (US)

(73) Assignee: Liquidity Corporation, Alameda, CA

(US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 133 days.

(21) Appl. No.: 14/750,251

(22) Filed: Jun. 25, 2015

(65) Prior Publication Data

US 2016/0251234 A1 Sep. 1, 2016

Related U.S. Application Data

- (60) Provisional application No. 62/121,605, filed on Feb. 27, 2015.
- (51) Int. Cl.

 C02F 1/00 (2006.01)

 B01D 39/14 (2006.01)

 B01D 29/35 (2006.01)

 B01D 39/16 (2006.01)

 B01D 39/20 (2006.01)

 B01D 71/42 (2006.01)

 (Continued)

(10) Patent No.: US 9,636,613 B2

(45) **Date of Patent:** May 2, 2017

B01D 39/2017 (2013.01); B01D 71/42 (2013.01); C02F 1/002 (2013.01); C02F 1/44 (2013.01); B01D 2239/025 (2013.01); B01D 2239/0442 (2013.01); B01D 2239/065 (2013.01); B01D 2239/1233 (2013.01); C02F 2101/12 (2013.01); C02F 2303/04 (2013.01); C02F 2307/02 (2013.01)

(58) Field of Classification Search

CPC C02F 1/002; C02F 1/003; C02F 2307/02 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

	3,335,917 A	*	8/1967	Knight		
	5.601.199 A	*	2/1997	Marty		210/453 A61J 9/00
	, ,			,		215/11.1
(Continued)						

Primary Examiner — Matthew O Savage (74) Attorney, Agent, or Firm — Locke Lord LLP; Scott D. Wofsy

(57) ABSTRACT

A portable bottle for filtering drinking water is disclosed that includes a bottle having a threaded opening, a cover for cooperating with the threaded opening of the bottle and including a top wall having a plurality of internal engagement lugs depending downwardly from an interior surface of the top wall, a filter cartridge including an end cap having a circumferential side wall that includes a plurality of engagement ribs for cooperating with the engagement lugs of the cover, and a spout including a compressible circumferential flange configured to be positioned between the interior surface of the top wall of the cover and the upper surface the end cap of the filter cartridge to provide a resilient biasing force therebetween.

20 Claims, 9 Drawing Sheets

